



## DESCRIPTION:

PEAK® AUTOMATIC TRANSMISSION FLUID is formulated with select highly refined base oils and specially balanced additives to meet the demands placed on automatic transmissions. PEAK® AUTOMATIC TRANSMISSION FLUID contains special friction modifiers that provide smooth lock-ups required by both General Motors and Ford. Its high viscosity index permits use over a wide temperature range by providing excellent low temperature fluidity while retaining the desired viscosity at high temperatures.

## BENEFITS:

- Helps provide smooth shift performance where DEXRON® III or a MERCON® fluid is specified
- Designed to provide outstanding high temperature oxidation resistance
- Offers excellent protection against corrosion, wear and rust
- Compatible with automatic transmission components such as elastomer seals and plastic parts

## APPLICATION:

PEAK® AUTOMATIC TRANSMISSION FLUID is recommended for use in automatic transmissions of General Motors, Ford (except those that specify Ford M2C33-F Type F fluids) and other U.S. and import vehicles requiring GM DEXRON IIIH, III, IIE, II, Ford MERCON ATF and Allison C4, TES 389.

Always consult your owner's manual for automatic transmission fluid requirements.



## SHIPPING INFORMATION:

Pack	6/1 Quart	3/1 Gallon	5 Gallon Pail	55 Gallon Drum	Bag in a Box
Unit Weight (lbs.)	2.1	8.15	40.6	450	43
Case/Pallet Weight*	12.3/1,973	24.45/1,517	1,755.2	1,850	1806**
Units per Pallet	936	180	42	4	-
Cases per Pallet	156	60	-	-	42
Units per Truck	20,592	3,780	882	84	-
Cases/Pallets per Truck	3,432/22	1,260/21	21	21	924/22
Case Size (inches)	9.5 x 7.6 x 9.6	12.5 x 7.9 x 11.9	-	-	19 x 13 x 7.25
Cases per row/Rows high	26/6	15/4	14/3	-	7/6
Pallet Size (inches)	48 x 40 x 61.4	48 x 40 x 55.8	44 x 49 x 51.1	46 x 48 x 40.5	40 x 48

(\*) Including pallet weight of 50lbs.

## PRODUCT INFORMATION:

Test (Method)	ATF Dexron®III/Mercon®		ATF Dexron®III/Mercon®		
API Gravity (ASTM D1298)	32.98		1 Quart Part Number	PDT0076	
Flash Point, °C (ASTM D93)	192		1 Gallon Part Number	PDT003	
Pour Point, °C (ASTM D97)	-46		6 Gallon Bag-in-Box	PDT00BX6	
Viscosity			5 Gallon Pail	PDT005	
'@ 40 °C, cSt (ASTM D445)	35.22		55 Gallon Drum	PDT001	
'@ 100 °C, cSt (ASTM D445)	7.29		Bulk	PDT000	
Viscosity Index (ASTM D2270)	179				
Dielectric Strength, kV, (ASTM D-877 Proc. A)	>35				
	<b>PDT0076</b>	<b>PDT003</b>	<b>PDT00BX6</b>	<b>PDT005</b>	<b>PDT001</b>
Individual UPC Code	0-74804-01314-6	0-74804-05178-0	-	0-74804-02054-0	0-74804-03403-5
Case UPC Code	0-74804-14803-9	0-74804-15178-7	-	-	-
Case SCC-14 Code	1-00-74804-04803-9	1-00-74804-05178-7	-	-	-
Bag in a Box UPC Code	-	-	0-74804-06274-8	-	-



Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2016 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC. Ver 202003

**RUN TRUE™**